SURTRON®

50 D // 80 D



50 D



SURTRON® 50 D is a radiofrequency electrosurgical unit suitable for minor monopolar surgery.

SURTRON® 50 D through the functions selection makes pure cut, cut coagulation (CUT 1 - CUT 2) and pure coagulation possible. The on-board microcontroller and digital display guarantees consistent safety and reliability under any conditions. SURTRON® 50 D offers outstanding professional surgical results due to its ergonomic and superior safety features.

10100.051

50 W – 400 Ω

45 W - 400 Ω

40 W – 400 Ω

40 W – 400 Ω

115/230 Vac

190x85x239

600 kHz

50-60 Hz

280 VA

2,5 Kgs

Reference code
Maximum output power CUT
Maximum output power CUT/COAG1
Maximum output power CUT/COAG2
Maximum output power COAG
Working frequency
Patient circuit
Selectable input voltage
Mains frequency
Electrical input power
Size WxHxD mm
Weight

80 D



SURTRON® 80 D is a radiofrequency electrosurgical unit suitable for minor monopolar surgery.

SURTRON® 80 D has a multi-function selector which makes cutting (CUT), cut coagulation (BLEND), coagulation (COAG) and micro-coagulation (MICRO) possible. The one-board microcontroller and digital display guarantees consistent safety and reliability under any conditions. SURTRON® 80 D offers outstanding professional surgical results due to its ergonomic and superior safety features.

Reference code
Maximum output power CUT
Maximum output power BLEND
Maximum output power COAG
Maximum output power MICRO
Working frequency
Patient circuit
Selectable input voltage
Mains frequency
Electrical input power
Size WxHxD mm
Weight

10100.081 80 W - 400Ω 60 W - 400Ω 50 W - 400Ω 20 W - 600Ω 700 kHz F 115-230 Vac 50-60 Hz 220 VA 190x85x239 2,5 Kgs







SAFETY

EN60601-1 EN60601-1-2 EN60601-2-2 Electrical Class: I CF MDD 93/42/EC Class: II b

CONTROLS

Patient/Plate circuit monitoring (80D) Output power monitoring Self check control